

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
13 October 2005 (13.10.2005)

PCT

(10) International Publication Number
WO 2005/096343 A1

(51) International Patent Classification⁷: **H01J 37/09**

(74) Agents: ZIMMERMANN, Gerd et al.; Zimmermann & Partner, P.O. Box 330 920, 80069 Munich (DE).

(21) International Application Number:
PCT/EP2005/001637

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 17 February 2005 (17.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
04006692.0 19 March 2004 (19.03.2004) EP

(71) Applicant (for all designated States except US): ICT, INTEGRATED CIRCUIT TESTING GESELLSCHAFT FÜR HALBLEITERPRÜFTECHNIK mbH [DE/DE]; Ammerthalstr. 20a, 85551 Heimstetten (DE).

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,


(72) Inventor; and

(75) Inventor/Applicant (for US only): FROSIEN, Jürgen [DE/DE]; Kufsteinerstrasse 16a, 85521 Riemerling (DE).

[Continued on next page]

(54) Title: HIGH CURRENT DENSITY PARTICLE BEAM SYSTEM

(57) Abstract: The present invention relates to charged particle beam devices. The devices comprise an emitter (12) for emitting charged particles; an aperture arrangement (26; 86) with at least two apertures (36) for separating the emitted charged particles into at least two independent charged particle beams; and an objective lens (18) for focusing the at least two independent charged particle beams, whereby the independent charged particle beams are focused onto the same location within the focal plane.





SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*